

UNI PLAY CLIMBOO 0412

THRE PASSAGE



Minimal space

Device Specifications	
Safety zone	17,22 m ²
Length	2,42 m
Width	0,88 m
Total height	1,21 m
Free fall height	< 0,60 m
Age range	3-14 years
In accordance w/ EN standards	1176-1:2017
Weight of the heaviest part [kg]	11
Dimension of the biggest part [cm]	176x8x8
Availability of spare parts	Yes

5,42

Material Specification

- Stainless steel or galvanized and powder coated steel 80 x 80 mm construction;
- Panels are made of atmospheric condition resistant HDPE plates;
- Platforms are made of anti-slip and waterproof plywood or HPL plate;
- · All screws covered with colorful plastic caps;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Top of the construction is secured with safe rubber caps;
- · Double wall tube passage made of polypropylene;

Additional comments

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface: 80/70/60 cm;
- The equipment is designed for public playgrounds; The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not its actual appearance. The colours may differ from those demonstrated on render.

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf/soil(A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,36 m (A,B,C)