

UNI PLAY NETTIX 1635

PLAYGROUND EQUIPMENT



Device Specifications	
Safety zone	22,23 m ²
Length	2,58 m
Width	2,24 m
Total height	2,23 m
Free fall height	2,00 m
Age range	4-14 years
In accordance w/ EN standards	1176-1:2017
Weight of the heaviest part [kg]	27
Dimension of the biggest part [cm]	10x10x300
Availability of spare parts	Yes

5,63 2,58 2,58

Minimal space

Material Specification

- 100 x 100 mm galvanized and/or powder coated steel construction;
- · Anti-slip and weather resistant HPL platforms;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Steel ropes braided with PP, connected by durable plastic elements;
- Top of the construction is secured with rubber caps;
- All screws, connectors and joints covered with plastic caps;
- Certified stainless steel chains:

Additional comments

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface : 80/70 cm;
- The equipment is designed for public playgrounds; Specification of the equipment, but not its actual appearance. The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not its actual appearance.

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 2,00 m (A,B,C)

Adress: Building E, Wisniowy Business Park, UI Ilzecka 26, 02-135, Warsaw, Poland Tell:+48 221 530 191

Email: info@uniplay.com.pl