

UNI PLAY SPRING 0604-1

HORSE SPRING RIDER



Device Specifications	
Safety zone	10,18 m ²
Length	0,78 m
Width	0,21 m
Total height	0,77 m
Free fall height	< 0,60 m
Age range	1-12 years
In accordance w/ EN standards	1176-1:2017
Weight of the heaviest part [kg]	23
Dimension of the biggest part [cm]	78x116x22
Availability of spare parts	Yes

3,78 0,78 12,6 12,6 12,6 12,6 12,6 13,7 14,0 15,6 15,6 16,7

Minimal space

Material Specification

- · Steel spring 20mm, iron phosphorated and powder coated;
- The seat and other elements are made of atmospheric condition resistant HDPE plates;
- All screws covered with plastic caps;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- · Other galvanized and/or powder coated metal elements;
- Colorful and ergonomic durable handles and footrests;

Additional comments

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface : 40 cm;
- The equipment is designed for public playgrounds; specification of the equipment, but not its actual appearance. The colours may differ from those demonstrated on render.

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf, soil (A,B), sand with minimal layer thickness of 30 cm (A), synthetic material approved for free fall of 0,60 m (A,B)