

UNI PLAY SPRING 0670

PANDA SPRING RIDER



| Device Specifications | | Minimal space | | |
|------------------------------------|----------------------|---------------|--------------|---------|
| Safety zone | 13,58 m ² | 6,33 | | |
| Length | 3,33 m | | | |
| Width | 0,28 m | 3,33 | | |
| Total height | 0,85 m | • • • • | | |
| Free fall height | < 0,60 m | | < | |
| Age range | 1-12 years | | \backslash | |
| In accordance w/ EN standards | 1176-1:2017 | | | <u></u> |
| Weight of the heaviest part [kg] | 19 | | | 2,2 |
| Dimension of the biggest part [cm] | 6x8x333 | | | |
| Availability of spare parts | Yes | | | . ↓ |

Material Specification

- Steel spring 20 mm, iron phosphorated and powder coated;
- Colorful, durable elements made of a tmospheric condition resistant HDPE plate;
- All screws covered with colorful plastic caps;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Galvanized and/or powder coated steel construction;
- Colorful and ergonomic, durable handles and footrests;

Additional comments

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface : 40 cm;
- The equipment is designed for public playgrounds; specification of the equipment, but not its actual appearance. The colours may differ from those demonstrated on render.

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf, soil (A,B), sand with minimal layer thickness of 30 cm (A), synthetic material approved for free fall of 0,60m (A,B)