


UNI PLAY SWING ST0512










Device Specifications	
Safety zone	29,83 m ²
Length	0,35 m
Width	4,38 m
Total height	1,79 m
Free fall height	0,99 m
Age group	1-3/3-14 years
In accordance w/ EN standards	1176-1:2017
Weight of the heaviest part [kg]	12
Dimension of the biggest part [cm]	225x8x8
Availability of spare parts	Yes



Material specification

- Galvanized and/or powder coated steel 80 x 80 mm construction;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Stainless steel screws or screws covered with plastic caps;
- Top of the construction is secured with rubber caps;
- Stainless steel chain hooks;
- Calibrated chain preventing fingers from getting stuck;
- Durable certified seats;

Additional information

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface : 80/70/60 cm;

• The equipment is designed for public playgrounds; The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not its actual appearance. The colours may differ from those demonstrated on render.

Available with different seat options: R1 - flat, R2 - baby seat, R3 - flat belt, R5 - flat with back rail;

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: turf/soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,99 m (A,B,C)